



FIRE RESISTANT STEEL DOOR

MFD033 FIRE RESISTANT STEEL DOOR FG EI60, WITH WOOD-EFFECT LAMINATED STEEL

Version 07

Recommended use

Used as door between fire stop sections in industrial buildings, dwellings and office buildings, where fire resistance class of door must be EI60.

Dimensions

The maximum dimensions of the door frame, mm: **1130 x 2430** or **1150 x 2390**.

Certificate of conformity

The door has been tested in accordance with the provisions of test standard EVS-EN 1634-1:2002 in a testing laboratory of TÜV NORD Baltik OÜ in Tallinn, and certified in accordance with the provisions of standard EVS-EN 13501-2:2004 by a certification bureau EstCert OÜ. The door holds a certificate no 153-065/08 with fire resistance grade EI₂60. The noise resistance (R' W) of the door according to the test standard EVS-EN ISO 140-14:2004 is 37 dB.

Construction

The door is manufactured of cold rolled galvanized Swedish sheet steel covered with wood pattern PVC film with stamping, edging and welding. Hinges are two screw-on sheet hinges with ball bearing. Diameter of hinge axis is 14 mm. Security elements are security pins and lock boxes reaching into door sheet. Two safety joint-pins 12 mm in diameter are placed between the hinges.

Door sheet is 64 mm thick. Jacket edges are at sides and top.

External and internal side are made of 1,25 mm thick cold rolled sheet steel. Tin sheets of the door sheet are on jointed with rivet seams. Inside the door sheet, there is isolation material in the form of fire-proof stone wool and mineral plate. The high rigidity of the door panel is achieved via glueing together the metal and the insulation material.

Sash is made of 1,5 mm profiles of cold rolled sheet steel, connected in sash corners with welds. Insulation is rock wool. Sash can be ordered with cover slat covering lateral installation slots (type XM) or solution without cover slat, for installation deeper than wall surface (type XS) The packing of the door is made of a 2x20 mm expanding gasket fastened to the doorjamb and an elastic silicone rubber gasket fastened into the groove of the doorjamb.

The door sill is made of hot-zincd or painted sheet steel.

Finish

Door sheet can be ordered in five different tones of wood pattern: oak (PVC1033), ash (PVC1227), walnut (PVC1066) and mahogany (PVC1157) beech. Sash is primed with epoxy paint and covered with polyurethane paint with tone suitable for wood pattern.

Locking

Usage locks of well-known lock manufacturers Abloy, Boda, Assa, and Nemeff. Locks certified as fire locks can be installed to the door.

Installation

Sash is fixed in seven points with connectors and hexagonal screws 8 x 100 mm. Connector aperture diameter is 10,5 mm. Fixing apertures are covered with plastic plugs with diameter 19 mm. The plat band is secured with a male screw 6,3 x 60 mm in the middle.

After fixing the installation, the door sash and the installation clearance are filled with stone wool or construction foam and are covered with a protective cleat of sheet metal of the same color as the door sash. Package includes fixing screws, connectors and plugs. For more details see installation manual.

Accessories

The door can be improved and completed with following accessories:
 - stainless steel or galvanized steel threshold, foot sheet, border slats, eyehole, security chain, stainless steel hinges, core, core covers, door handle, lock casing;
 - Window, the maximum dimension of the lighting opening 510 x 530 mm minimum distance from the edge of the door sheet is 240 mm, may take up to 25% of the surface area.
 Catch with non-detachable arm must be installed to the door located in evacuation path. Catch Abloy DC405BC can be used.

Maintenance

Door must be checked and maintained at least in every six months. Check closing of door and operation of locking elements. Detailed information is available in maintenance manual. It is possible to sign a maintenance contract upon purchasing the door.

